



	RATED 2 TONNES	RATED 2.8 TONNES	RATED 4 TONNES	RATED 6 TONNES
MOT Approval for	Class 4	Class 7		
Part No. Manual	HPJ2	HPJ2.8	HPJ4	N/A
Part No. Air/Hydraulic	MPJ2	MPJ2.8	MPJ4	MPJ6
A Width when extended	1700mm – 67'	1700mm – 67'	1605mm – 63'	1300mm – 51'
B Width when retracted	800mm – 31.5'	815mm – 32'	864mm – 34'	910mm – 35.8'
C Minimum width over support arms	775mm – 30.5'	790mm – 31'	830mm – 32.5'	920mm – 36.2'
D Maximum width over support arms	1125mm – 44'	1130mm – 44.5'	1300mm – 51'	1290mm – 50.7'
E Closed height	212mm – 8.25'	242mm – 9.5'	261mm – 10.25'	320mm – 12.6'
F Total lift	260mm – 10.25'	260mm – 10.25'	205mm – 8'	200mm – 7.8'
*G Height above platform/floor	75mm – 2.9'	92mm – 3.6'	97mm – 3.8'	101mm – 3.9'
*can be set lower with special arms if required				
Weight – with top beam	87kgs – 192lbs	113kgs – 249lbs	155kgs – 341lbs	224kgs – 494lbs

Narrow Jacking Beams to fit narrow pits and lifts (pump mounted externally)

C Minimum width over support arms	685mm – 27'	700mm – 27.58'	N/A	N/A
D Maximum width over support arms	1015mm – 40'	1020mm – 40.5'	N/A	N/A
OPTIONAL EXTRA WIDE TOP BEAM				
A Width when extended	1850mm – 73'	1850mm – 73'	N/A	N/A
B Width when retracted	950mm – 37.5'	963mm – 38'	N/A	N/A
RAISER BLOCKS				
Part No.	RATED 2 TONNES	RATED 2.8 TONNES	RATED 4 TONNES	RATED 6 TONNES
1532A	Standard	Standard	Standard	Standard
1526	Standard	Standard	Standard	N/A
1835	N/A	N/A	N/A	Standard
1836	N/A	N/A	N/A	Standard
1527	Optional	Optional	Standard	N/A
1532C	Optional	Optional	Optional	Optional
1532V	Optional	Optional	Optional	Optional